



# لیست قیمت داهوا ۱۴۰۵

 RAYAN  
NOVIN



	HFW-B2A21P	HFW-B1A21P-U-A	HFW-B1A21P-U	HDW-T1A51P-U	HDW-T2A21P-U-A	HDW-T1A21P-U
Resolution	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)
Microphone	--	Bult In Mic	--	--	Bult In Mic	--
Lens	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm
Viewing angle	117/94°	117/94°	117/94°	117/94°	117/94°	117/94°
Night vision type	B/W	B/W	B/W	B/W	B/W	B/W
IR Range	20m	30m	30m	30m	30m	30m
WDR	DWDR	DWDR	DWDR	DWDR	DWDR	DWDR
Compression format	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS
Body material	Metal	Plastic	Plastic	Plastic	Metal	Plastic
Degree of protection	IP67	IP67	IP67	--	IP67	--
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C
Voltage	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V
Price	35,600,000	31,000,000	28,700,000	40,900,000	40,300,000	28,700,000



HFW-1200CP

HDW-1200EMP-A

HDW1200TRQP-A

HFW-B2A21P-U-IL-A

HFW-B2A21P-U-A

HFW-B2A21P-U

Resolution

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

Microphone

--

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

--

Lens

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

Viewing angle

102/83°

99/83°

102/83°

117/94°

117/94°

117/94°

Night vision type

B/W

B/W

B/W

Dual Light

B/W

B/W

IR Range

30m

30m

30m

30m

30m

30m

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

DWDR

Compression format

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

Body material

Plastic

Metal

Plastic

Metal

Metal

Metal

Degree of protection

IP67

IP67

--

IP67

IP67

IP67

Temperature

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

Voltage

DC12V

DC12V

DC12V

DC12V

DC12V

DC12V

Price

28,300,000

-----

36,400,000

41,000,000

40,300,000

36,300,000



	HFW-1200DP	HFW-1200THP-I8	HFW-1200THP-I4	HFW-1200TP-A	HFW-1200TP	HFW-1200TLP
Resolution	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)
Microphone	--	--	--	Bult In Mic	--	--
Lens	3.6mm	3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm
Viewing angle	83°	84°	102/83°	102/83°	102/83°	102/83°
Night vision type	B/W	B/W	B/W	Dual Light	B/W	B/W
IR Range	80m	80m	40m	30m	30m	40m
WDR	DWDR	DWDR	DWDR	DWDR	DWDR	DWDR
Compression format	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS
Body material	Metal	Plastic & Metal	Plastic & Metal	Metal	Metal	Plastic
Degree of protection	IP67	IP67	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C
Voltage	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V
Price	50,100,000	35,000,000	33,000,000	-----	-----	-----



HFW-1200CMP-IL-A

HFW-1200CLP-IL-A

HDW-1200TLMP-IL-A

HDW-1239TLQP-IL-A

HDW-1209TLQP-A

HDW1200-CLQP-IL-A

Resolution

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

2MP(25/30fps)

Microphone

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Lens

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

Viewing angle

102/83°

102/83°

102/83°

101.8° /84.2°

106/86.9°

102/83°

Night vision type

Dual Light

Dual Light

Dual Light

Dual Light

Full Color

Dual Light

IR Range

20m

20m

20m

30m

30m

20m

WDR

DWDR

DWDR

DWDR

120db

DWDR

DWDR

Compression format

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

Body material

Metal

Plastic

Metal

Plastic & Metal

Plastic & Metal

Plastic

Degree of protection

IP67

IP67

IP67

IP67

IP67

IP67

Temperature

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

Voltage

DC12V

DC12V

DC12V

DC12V

DC12V

DC12V

Price

49,200,000

43,500,000

51,000,000

52,000,000

47,600,000

41,700,000



	HDW-1500TRQP-A	HFW-1239TLMP-IL-A	HFW-1209TLMP	HFW-1209CP-A	HFW-1209CP	HFW-1239CP-IL-A
Resolution	5MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)
Microphone	Bult In Mic	Bult In Mic	--	Bult In Mic	--	Bult In Mic
Lens	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm
Viewing angle	111/92°	101.8° /84.2°	103.6° /86.9°	106/86.9°	117/94°	108/86°
Night vision type	B/W	Dual Light	Full Color	Full Color	Full Color	Dual Light
IR Range	30m	40m	40m	20m	20m	20m
WDR	DWDR	120db	DWDR	DWDR	DWDR	120db
Compression format	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS
Body material	Plastic	Plastic & Metal	Plastic & Metal	Plastic	Plastic	Plastic
Degree of protection	--	IP67	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C
Voltage	DC12V	DC12V	DC12V	DC12V	DC12V	DC12V
Price	51,400,000	63,700,000	50,800,000	39,500,000	37,700,000	43,500,000



HDW-1509TLQP-A

HFW-1500DP

HFW-1500CMP-A

HFW-1500TP-A

HFW-1500CP

HDW-1500TMQP-A

Resolution

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

Microphone

Bult In Mic

--

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Lens

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

Viewing angle

112/92°

111/92°

111/92°

111/92°

111/92°

111/92°

Night vision type

Full Color

B/W

B/W

B/W

B/W

B/W

IR Range

20m

80m

30m

30m

30m

50m

WDR

120db

DWDR

DWDR

DWDR

DWDR

DWDR

Compression format

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

Body material

Plastic & Metal

Metal

Metal

Metal

Plastic

Plastic & Metal

Degree of protection

IP67

IP67

IP67

IP67

IP67

IP67

Temperature

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

Voltage

DC12V

DC12V

DC12V

DC12V

DC12V

DC12V

Price

83,300,000

73,300,000

51,480,000

50,500,000

38,600,000

65,400,000



HFW-1509TLMP

HFW-1509TP

HDW-1509TP-IL-A

HDW-1500TLMP-IL-A

HDW-1500CLQP-IL-A

HDW-1509TP-A

Resolution

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

5MP(25/30fps)

Microphone

--

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Lens

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

2.8mm/3.6mm

Viewing angle

112/88°

112/88°

111/89°

113.3° /90.1°

113.3° /90.1°

112/92°

Night vision type

Full Color

Full Color

Dual Light

Dual Light

Dual Light

Full Color

IR Range

40m

20m

20m

40m

20m

20m

WDR

120db

120db

120db

120db

DWDR

120db

Compression format

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

CVI /TVI / AHD  
CVBS

Body material

Plastic & Metal

Metal

Metal

Metal

Plastic & Metal

Metal

Degree of protection

IP67

IP67

IP67

IP67

IP67

IP67

Temperature

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

Voltage

DC12V

DC12V

DC12V

DC12V

DC12V

DC12V

Price

83,100,000

82,100,000

103,600,000

65,000,000

60,200,000

88,200,000



	HFW-1509TLMP-IL-A	HFW1500-TLMP-IL-A	HFW1509-TLMP-A	HAC-B1A21	HAC-B1A41	HAC-B1A51-S2
Resolution	5MP(25/30fps)	5MP(25/30fps)	5MP(25/30fps)	2MP 1/2.7"	4MP 1/2.7"	5MP 1/2.7"
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	N/A	N/A	N/A
Lens	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2MP 3.6mm fixed	4MP 3.6mm fixed	5MP 2.8 & 3.6mm fixed
Viewing angle	113.3° /90.1°	113.3° /90.1°	112/88°	93°	89°	106° /88°
Night vision type	Dual Light	Dual Light	Full Color	Smartir	Smartir	Smartir
IR Range	40m	40m	40m	20m	20m	20m
WDR	120db	120db	120db	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC
Compression format	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI /TVI / AHD CVBS	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI
Body material	Plastic & Metal	Plastic & Metal	Plastic & Metal	Plastic	Plastic	Plastic
Degree of protection	IP67	IP67	IP67	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C
Voltage	DC12V	DC12V	DC12V	±30%DC12V/2.7W	±30%DC12V/3.7W	±30%DC12V/3.7W
Price	89,900,000	69,600,000	86,100,000	28,700,000	34,600,000	41,700,000



	HAC-T1A21	HAC-T1A41	HAC-T1A51	HAC-T2A21	HAC-T2A41	HAC-T2A51
Resolution	2MP 1/2.7"	4MP 1/2.7"	5MP 1/2.7"	2MP 1/2.7"	4MP 1/2.7"	5MP 1/2.7"
Microphone	N/A	N/A	N/A	N/A	N/A	N/A
Lens	2MP 2.8 & 3.6mm fixed	4MP 2.8mm fixed	5MP 2.8 & 3.6mm fixed	2MP 2.8mm fixed	4MP 2.8mm fixed	5MP 2.8 & 3.6mm fixed
Viewing angle	1100° /80°	105°	106° /88°	100°	105°	106° /88°
Night vision type	Smartir	Smartir	Smartir	Smartir	Smartir	Smartir
IR Range	20m	20m	20m	20m	20m	20m
WDR	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC
Compression format	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI
Body material	Plastic	Plastic	Plastic	Aluminium	Aluminium	Aluminium
Degree of protection	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning
Temperature	- 40 ° C to + 60C	- 40 ° C to + 55C	- 40 ° C to + 55C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C
Voltage	±30%DC12V/2.7W	±30%DC12V/2.7W	±30%DC12V/2.7W	±30%DC12V/2.8W	±30%DC12V/3.7W	±30%DC12V/3.7W
Price	28,200,000	34,600,000	40,900,000	35,600,000	42,300,000	47,500,000



	HAC-B2A41	HAC-B2A51	HAC-B2A21-U-IL	HAC-B2A51-U-IL-S2	HAC-T1A21-U-IL-A	HAC-T2A51-U-IL-A
Resolution	4MP 1/2.7"	7MP 1/2.7"	2MP 1/2.7"	5MP 1/2.7"	2MP 1/2.7"	5MP 1/2.7"
Microphone	N/A	N/A	N/A	N/A	Bult In Mic	Bult In Mic
Lens	4MP 3.6mm fixed	5MP 3.6mm fixed	2MP 3.6mm fixed	5MP 3.6mm fixed	2MP 2.8mm fixed	5MP 2.8mm fixed
Viewing angle	89°	77.5°	80°	92°	100°	106°
Night vision type	Smartir	Smartir	Smart Dual Light +	Smart Dual Light +	Smart Dual Light +	Smart Dual Light +
IR Range	20m	20m	IR 30m/Warmlight 20m	IR 30m/Warmlight 20m	IR 25m/Warmlight 20m	IIR 30m/Warmlight 30m
WDR	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC	DWDR, BLC, HLC, 2D DNR, AWB, AGC
Compression format	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI	CVI/CVBS/AHD/TVI
Body material	Aluminium	Aluminium	Metal	Metal	Plastic	Metal
Degree of protection	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning	IP67/4KV Lightning	Basic Protection	IP67/4KV Lightning
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C
Voltage	±30%DC12V/3.7W	±30%DC12V/3.9W	±30%DC12V/3.3W	±30%DC12V/4.0W	±30%DC12V/2.1W	±30%DC12V/4.0W
Price	42,300,000	48,700,000	41,000,000	54,900,000	33,900,000	56,900,000



HFW1500R-Z-S2

HFW1209CM-LED

HFW1239TLM-A-LED

HDW1509TLQ-A-LED-S2

HFW1509MH-A-LED-S2

HFW1809TLM-A-LED

Resolution

5MP 1/2.7"

2MP 1/2.8"

2.16MP 1/2.8"

5MP 1/2.7"

5MP 1/2.7"

4K 1/2.7"

Microphone

N/A

N/A

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Lens

5MP 2.7-12mm Motorized

2MP 2.8mm fixed

2MP 3.6mm fixed

5MP 3.6mm fixed

5MP 3.6mm fixed

4K 3.6mm fixed

Viewing angle

107° - 34°

106°

86°

88°

88°

85°

Night vision type

Smart IR

Smart LED

Smart LED

Smart LED

Smart LED

Smart LED

IR Range

60m

20m

40m

20m

50m

40m

WDR

DWDR, BLC, HLC, 2D DNR, AWB, AGC

DWDR, BLC, HLC, 2D DNR, AWB, AGC

DWDR, BLC, 2D DNR, AWB, AGC, E-Defog, 16X Digital Zoom

WDR 120db | HLC Pro 3D DNR | SUPER ADAPT

WDR 120db | HLC Pro 3D DNR | SUPER ADAPT

WDR 120db | HLC Pro 3D DNR | E-Defog SUPER ADAPT

Compression format

CVI/CVBS/AHD/TVI

CVI/CVBS/AHD/TVI

CVI/CVBS/AHD/TVI

CVI/CVBS/AHD/TVI

CVI/CVBS/AHD/TVI

CVI/CVBS/AHD/TVI

Body material

Metal

Metal

Metal+Plastic

Metal+Plastic

Metal+Plastic

Metal+Plastic

Degree of protection

IP67/4KV Lightning

IP67/4KV Lightning

IP67/4KV Lightning

IP67/4KV Lightning

IP67/4KV Lightning

IP67/4KV Lightning

Temperature

- 30 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 40 ° C to + 55C

- 40 ° C to + 60C

- 40 ° C to + 60C

Voltage

±30%DC12V/9.8W

±30%DC12V/3.1W

±30%DC12V/5W

±30%DC12V/4.4W

±30%DC12V/6.4W

±30%DC12V/6.9W

Price

114,100,000

47,800,000

63,700,000

83,300,000

91,000,000

124,600,000



PT1500A-IL-A

PT1509A-A-LED

SD49225I-HC-LA

SD59225I-HC-S2

SD59230I-HC

Resolution

5MP 1/2.7"

5MP 1/2.7"

STARVIS 2MP 1/2.8"

Exmor R 2MP 1/2.8"

Exmor R 2MP 1/2.8"

Microphone

Bult In Mic

Bult In Mic

Audio in 1ch  
Alarm I/O 1/2  
RS1 485

Audio in 1ch  
Alarm I/O 1/2  
RS1 485

Audio in 1ch  
Alarm I/O 1/2  
RS1 485

Lens

5MP 2.8mm fixed

5MP 2.8mm fixed

2MP 4.8-120mm

2MP 4.8-120mm

2MP 4.5-135mm

Viewing angle

111°

111°

62.8° ~ 2.6°

62.8° ~ 2.6°

67.8° ~ 2.4°

Night vision type

Smart Dual Light +

Smart LED

Smart IR

Smart IR

Smart IR

IR Range

IR 40m/Warmlight 40m

IR 40m/Warmlight 40m

100m

150m

150m

WDR

Smart Area Lighting  
**SUPER ADAPT**

WDR 120db | HLC Pro | 3D DNR  
E-Defog | 4x Digital Zoom  
**SUPER ADAPT**

WDR 120db | HLC/BLC  
2D/3D DNR | Defog | 16x  
Digital Zoom

WDR 120db | HLC/BLC  
2D/3D DNR  
16x Digital Zoom

WDR 120db | HLC/BLC  
2D/3D DNR  
16x Digital Zoom

Compression format

CVI/CVBS/AHD/TVI

CVI/CVBS/AHD/TVI

CVI/CVBS

CVI/CVBS

CVI/CVBS

Body material

Plastic

Plastic

Metal

Metal

Metal

Degree of protection

IP66/4KV Lightning

IP67/4KV Lightning

IP66/4KV Lightning

IP66/6KV Lightning

IP66/6KV Lightning

Temperature

- 40 ° C to + 60C

- 40 ° C to + 55C

- 40 ° C to + 70C

- 40 ° C to + 70C

- 40 ° C to + 70C

Voltage

±30%DC12V/6.4W

±30%DC12V/7.7W

±30%DC12V/3A

±30%AC24V/3A

±30%AC24V/3A

Price

103,600,000

126,000,000

510,500,000

547,400,000

639,800,000



	XVR5108HS-I3	XVR5104HS-I3	XVR1B16-I	XVR1B08-I	XVR1B04H-I	XVR1B04-I
Compression format	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+
Number of CVI channel	8CH	4CH	16CH	8CH	4CH	4CH
Number of IP channel	4CH	2CH	2CH	2CH	2CH	2CH
Recording quality	5M-N/4M-N/1080P	5M-N/4M-N/1080P	1080N/720P	1080N/720P	5M-N/4M-N/1080P	1080N/720P
Recording based frame rate	15fps@1080P	15fps@1080P	25/30fps@1080N	25/30fps@1080N	25/30fps@1080N	25/30fps@1080N
BandWidth	64Mbps	32Mbps	64Mbps	40Mbps	32Mbps	20Mbps
Screen output	HDMI/VGA(1920*1080)	HDMI/VGA(1920*1080)	HDMI/VGA(1920*1080)	HDMI/VGA(1920*1080)	HDMI/VGA(1920*1080)	HDMI/VGA(1920*1080)
SD Card	16TB	16TB	16TB	16TB	6TB	6TB
Number of network port	1*100M	1*100M	1*100M	1*100M	1*100M	1*100M
Number of USB port	2 USB2.0	2 USB2.0	2 USB2.0	2 USB2.0	2 USB2.0	2 USB2.0
Voltage	DC12V/2A	DC12V/2A	DC12V/2A	DC12V/2A	DC12V/2A	DC12V/2A
Price	215,000,000	153,000,000	176,000,000	114,900,000	92,500,000	90,500,000



	XVR5108HS-4KL-I3	XVR5104HS-4KL-I3	XVR5116HS-I3	XVR5232AN-I3	XVR5216AN-I3	XVR5216AN-4KL-I3
Compression format	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+	AI Coding/H.265+
Number of CVI channel	8CH	4CH	16CH	32CH	16CH	16CH
Number of IP channel	2CH	2CH	8CH	16CH	8CH	8CH
Recording quality	5M-P/4M-P/1080P	5M-P/4M-P/1080P	5M-N/4M-N/1080P	5M-N/4M-N/1080P	5M-N/4M-N/1080P	5M-P/4M-P/1080P
Recording based frame rate	12fps@5MP	12fps@5MP	15fps@1080P	15fps@1080P	25/30fps@1080N	12fps@5MP
BandWidth	128Mbps	64Mbps	128Mbps	128Mbps	128Mbps	128Mbps
Screen output	HDMI(3840*2160)/VGA	HDMI(3840*2160)/VGA	HDMI(3840*2160)/VGA	HDMI(3840*2160)/VGA	HDMI(3840*2160)/VGA	HDMI(3840*2160)/VGA
SD Card	16TB	16TB	16TB	2*16TB	2*16TB	2*16TB
Number of network port	1*1000M	1*1000M	1*1000M	1*1000M	1*1000M	1*1000M
Number of USB port	2 (1USB2.0 / 1USB3.0)	2 (1USB2.0 / 1USB3.0)	2 (1USB2.0 / 1USB3.0)	2 (1USB2.0 / 1USB3.0)	2 (1USB2.0 / 1USB3.0)	2 (1USB2.0 / 1USB3.0)
Voltage	DC12V/2A	DC12V/2A	DC12V/2A	DC12V/4A	DC12V/4A	DC12V/2A
Price	428,500,000	306,000,000	387,500,000	816,000,000	510,000,000	816,000,000



XVR1B08H-I

XVR4232AN-I

Video Compression

AI Coding/H.265+  
Dual Stream

AI Coding/H.265+  
Dual Stream

Type

8CH Penta-brid 1U DVR

32ch Penta-brid 2MN/1MP 1U DVR

Res/fps

5MN@10fps/4MN&1080P@15fps/  
1080N@30fps

--

Decode Capacity

8ch@1080N

1st ch 2MN/1MP@30fps  
others 2MN/1MP@15fps

N+M

Pentabrid 4+8 IP 6MP

16+16 IP 6MP

BandWidth

64Mbps

128Mbps

Audio Codec

G.711a; G.711u; PCM

--

Video Output

1 HDMI , 1 VGA 1080P

1 HDMI , 1 VGA 1080P, 1 CVBS

Network Interface

100/10Mbps

1000/100/10\*1Mbps

Number of USB port

2\*USB 2.0

1\*USB 1 ,2.0\*USB 3.0

Storage

1 SATA Port, up to 16TB

2 SATA Port, 16TB each(32TB Total)

Temp/Humidity

-10° ~ +45° C / 10 - 90%

-10° ~ +55° C / 10 - 90%

Voltage

12VDC/1.5A/7W

12VDC/4A/12W

Price

189,000,000

570,000,000



## فروش محصولات داهوا

📞 اکبر کشاورز ۰۹۱۲۹۴۹۴۲۳۴ | فاطمه واحدی ۰۹۹۰۲۷۰۶۲۵۷

🌐 [www.rayannovincctv.com](http://www.rayannovincctv.com) | 📷 [rayannovin.cctv](https://www.instagram.com/rayannovin.cctv)

📍 تهران، خیابان جمهوری، تقاطع شیخ هادی و رازی، مرکز تجاری یگانه، طبقه دوم، واحد ۲۱۱

 **RAYAN  
NOVIN**