



لیست قیمت داهوا ۱۴۰۵

 RAYAN
NOVIN



	HDW-2249TP-S-LED	HDW-1239VP-A-IL	HDW-1239T2P-A	HFW-2241SP-S	HFW-1230TL2P	HDW-1230T2P-A
Resolution	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	--	Bult In Mic
Lens	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	3.6mm	3.6mm
Viewing angle	106/85°	104/88°	87/71°	107/88°	79°	79°
Night vision type	Full Color	Dual Light	B/W	B/W	B/W	B/W
IR Range	30m	30m	30m	30m	30m	30m
WDR	120db	DWDR	DWDR	120db	DWDR	DWDR
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Plastic & Metal	Plastic & Metal	Plastic & Metal	Metal	Plastic & Metal	Plastic & Metal
SD Card	256 GB	--	--	256 GB	--	--
Degree of protection	IP67	IP67	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 50C
Voltage	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE
Price	102,000,000	108,000,000	-----	-----	75,000,000	-----



	HFW-3441EP-S	HFW-2441SP-S	HDW-1430T2P-A	HFW-2449SP-S	HFW-1239TL2P	HFW-1239TL1P-IL-A
Resolution	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	2MP(25/30fps)	2MP(25/30fps)
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	--	Bult In Mic
Lens	2.8mm/3.6mm	2.8mm/3.6mm	3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm
Viewing angle	103/84°	107/88°	76°	106/85°	87/71°	104/88°
Night vision type	B/W	B/W	B/W	Full Color	Full Color	Dual Light
IR Range	50m	30m	30m	30m	15m	30m
WDR	120db	120db	DWDR	120db	DWDR	DWDR
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal	Metal	Plastic & Metal	Metal	Plastic & Metal	Plastic & Metal
SD Card	256 GB	256 GB	--	256 GB	--	--
Degree of protection	IP67	IP67	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 50C
Voltage	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE
Price	-----	147,000,000	-----	168,300,000	94,500,000	100,200,000



	HDW-1439TL1P-A-IL	HFW-1439TL2P-S	HDW-3449TMP-AS	HDW-2449TP-S-IL	HDW-1439VP-A-IL	HFW-5442TP-ASE
Resolution	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	--	Bult In Mic
Lens	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm	2.8mm/3.6mm
Viewing angle	94/78°	94/78°	103° /80°	105/87°	94/87°	112/88°
Night vision type	Dual Light	Full Color	Full Color	Dual Light	Full Color	B/W
IR Range	30m	30m	30m	30m	30m	50m
WDR	120db	120db	120db	120db	120db	140db
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Plastic & Metal	Plastic & Metal	Metal	Plastic & Metal	Plastic & Metal	Metal
SD Card	--	--	256 GB	256 GB	--	256 GB
Degree of protection	IP67	IP67	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C
Voltage	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE
Price	135,600,000	130,000,000	243,500,000	169,500,000	135,700,000	-----



	HFW-2541SP-S	HFW-2449TP-ZAS-IL	HFW-3449T1P-AS-PV	HFW3449-EP-AS	HFW-2449TP-AS-IL	HFW-2449SP-S-IL
--	--------------	-------------------	-------------------	---------------	------------------	-----------------

Resolution	5MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)	4MP(25/30fps)
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic
Lens	2.8mm/3.6mm	2.7mm = 13.5mm	2.8mm/3.6mm	2.8mm/3.6mm	3.6mm	2.8mm/3.6mm
Viewing angle	111/92°	97/28°	101/82°	103° /80°	84°	95/78°
Night vision type	B/W	Dual Light	Dual Light	Full Color	Dual Light	Dual Light
IR Range	30m	60m	30m	30m	60m	50m
WDR	120db	120db	120db	120db	120db	120db
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal	Metal	Metal	Metal	Metal	Metal
SD Card	256 GB	256 GB	256 GB	256 GB	256 GB	256 GB
Degree of protection	IP67	IP67	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C
Voltage	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE
Price	175,000,000	372,800,000	358,600,000	233,500,000	225,500,000	168,300,000



	SD5A425GB-HNR	SD49425GB-HNR	HFW2849-T-AS-IL	H FW2841TP-ZS	HFW-2841TP-AS	HFW-1839TCP-A-IL
Resolution	4MP(25/30fps)	4MP(25/30fps)	8MP(25/30fps)	8MP(25/30fps)	8MP(25/30fps)	8MP(25/30fps)
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic
Lens	5mm=125mm	5mm=125mm	3.6mm	2.7mm=13.5mm	3.6mm	2.8mm/3.6mm
Viewing angle	63.1° - 3.7°	63.1° - 3.7°	87°	138/36°	88°	110/86°
Night vision type	B/W	B/W	Dual Light	B/W	B/W	Dual Light
IR Range	150m	100m	30m	60m	80m	30m
WDR	120db	120db	120db	120db	120db	120db
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal	Metal	Metal	Metal	Metal	Plastic & Metal
SD Card	512GB	512GB	256 GB	256 GB	256 GB	--
Degree of protection	IP67-IK10	IP66	IP67	IP67	IP67	IP67
Temperature	- 40 ° C to + 70C	- 40 ° C to + 70C	- 40 ° C to + 50C	- 40 ° C to + 60C	- 40 ° C to + 50C	- 40 ° C to + 60C
Voltage	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE	DC12V / POE
Price	175,000,000	372,800,000	358,600,000	233,500,000	225,500,000	168,300,000



HDW1431T1-A-S4

HFW1530S-S6

HDW2441T-S

HFW2441T-ZS

HDBW2441R-ZS

HFW2541T-AS-S2

Resolution

4MP 3/1"

5MP 1/2.7"

4MP 1/2.9"

4MP 1/2.9"

4MP 1/2.9"

5MP 1/2.7"

Microphone

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

Bult In Mic

1/1 + Bult In Mic

Lens

4MP 3.6mm fixed/M12

4MP 3.6mm fixed/M12

4MP 2.8mm fixed/M12

4MP 2.7-13.5mm
Motorized/M12

4MP 2.7-13.5mm
Motorized/M12

5MP 3.6mm fixed/M12

Viewing angle

81°

92°

95°

104° -29°

104° -29°

92°

Night vision type

Smart IR

Smart IR

Smart IR

Smart IR

Smart IR

Smart IR

IR Range

30m

30m

30m

4 IR LEDs/60m

2 IR LEDs/40m

4 IR LEDs/80m

WDR

True WDR 120db, BLC, HLC, 3D
DNR, AWB, AGC, Fixed IRIS, Rol,
Privacy Area

DWDR, BLC, HLC, 3D DNR, AWB,
AGC, Fixed IRIS, Rol, Privacy Area

True WDR 120db, BLC, HLC, 3D
DNR, AWB, AGC, Fixed IRIS, Rol,
Privacy Area

True WDR 120db, BLC, HLC, 3D
DNR, AWB, AGC, Fixed IRIS, Rol,
Privacy Area

True WDR 120db, BLC, HLC, 3D
DNR, AWB, AGC, Fixed IRIS, Rol,
Privacy Area

True WDR 120db, BLC, HLC, 3D
DNR, AWB, AGC, Fixed IRIS, Rol,
Privacy Area

Compression format

H.265+

H.265+

H.265+

H.265+

H.265+

H.265+

Body material

Metal+Plastic

Metal

Metal+Plastic

Metal

Metal

Metal

SD Card

FTP, SFTP, NAS

FTP

Micro SD 256GB, Dahua Cloud,
FTP, SFTP, NAS

Micro SD 256GB, Dahua Cloud,
FTP, SFTP, NAS

Micro SD 256GB, Dahua Cloud,
FTP, SFTP, NAS

Micro SD 256GB, Dahua Cloud,
FTP, SFTP, NAS

Degree of protection

IP67/4KV Lightning,
Cyber Security

IP67/4KV Lightning,
Cyber Security

IP67/4KV Lightning,
Cyber Security

IP67/IK10
4KV Lightning, Cyber Security

IP67/IK10
4KV Lightning, Cyber Security

IP67/IK10
4KV Lightning, Cyber Security

Temperature

- 40 ° C to + 55C

- 40 ° C to + 60C

- 40 ° C to + 60C

- 30 ° C to + 60C

- 30 ° C to + 60C

- 30 ° C to + 60C

Voltage

%30±DC12V/1.9W-
Max 3.8W

%30±DC12V/1.9W-
Max 3.8W

%30±DC12V/2.5W-
Max 4.2W

%30±DC12V/2.4W-
Max 8.7W

%30±DC12V/2.3W-
Max 6.4W

%30±DC12V/2.2W-
Max 7.4W

Price

125,100,000

136,000,000

148,000,000


294,000,000

285,000,000

250,000,000



	HFW3441T-ZS	HFW3541T-ZS	HDBW3441E-AS	HDBW3541E-S-S2	HFW5541E-ZE-S3	HDBW5541E-ZE-S3
Resolution	4MP 1/2.9"	5MP 1/2.7"	4MP 1/3"	5MP 1/2.7"	5MP 1/2.7"	5MP 1/2.7"
Microphone	Bult In Mic	Bult In Mic	1/1	Bult In Mic	1/1 Bult In Mic	1/1 Bult In Mic
Lens	4MP 13.5-2.7mm Motorized/φ 14	5MP 13.5-2.7mm Motorized/φ 14	4MP 2.8mm fixed/M12	5MP 2.8mm fixed/M12	5MP 2.7-13.5mm Motorized/φ 14	5MP 2.7-13.5mm Motorized/φ 14
Viewing angle	104° -29°	99° -28°	103°	111°	114° -32°	114° -32°
Night vision type	Smart IR	Smart IR	Smart IR	Smart IR	Smart IR	Smart IR
IR Range	4 IR LEDs/60m	4 IR LEDs/60m	3 IR LEDs/50m	3 IR LEDs/50m	4 IR LEDs/60m	3 IR LEDs/40m
WDR	EIS, Defog, AFSA, Ai SSA, True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	EIS, Defog, AFSA, Ai SSA, True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal	Metal	Metal	Metal	Metal	Metal
SD Card	Micro SD 256GB, Dahua Cloud, FTP, SFTP, NAS	Micro SD 512GB, Dahua Cloud, FTP, SFTP, NAS	Micro SD 256GB, Dahua Cloud, FTP, SFTP, NAS	Micro SD 512GB, Dahua Cloud, FTP, SFTP, NAS	Micro SD 1TB, Dahua Cloud, FTP, SFTP, NAS	Micro SD 1TB, Dahua Cloud, FTP, SFTP, NAS
Degree of protection	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67/IK10 4KV Lightning, Cyber Security	IP67/IK10 4KV Lightning, Cyber Security	IP67/IK10 4KV Lightning, Cyber Security	IP67/IK10 4KV Lightning, Cyber Security
Temperature	- 30 ° C to + 60C	- 30 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 30 ° C to + 60C	- 30 ° C to + 60C
Voltage	%30±DC12V/2.8W- Max 7.9W	%30±DC12V/2.8W- Max 7.4W	%30±DC12V/2.2W- Max 7.3W	%30±DC12V/4W- Max 8.5W	%30±DC12V/3.6W- Max 10.4W	%30±DC12V/3.9W- Max 10.4W
Price	327,000,000	391,000,000	201,500,000	252,000,000	495,000,000	556,000,000



	HFW5442E-Z4E	HFW1239S1-A-LED-S5	HFW1439S1-A-LED-S4	HFW1239TC1-LED-S6	HFW3549E-AS-LED	HFW5449T1-ZE-LED
Resolution	4MP 1/1.8"	2MP 1/2.8"	4MP 1/3"	2MP 1/2.8"	5MP 1/2.7"	4MP 1/1.8"
Microphone	1/1 Bult In Mic	Bult In Mic	Bult In Mic	N/A	N/A	1/1 Dual Built-in Mic & Speaker
Lens	4MP 8-32mm Motorized/Module	2MP 2.8mm fixed/M12	4MP 3.6mm fixed/M12	2MP 3.6mm fixed/M12	5MP 3.6mm fixed/M12	4MP 2.7-12mm Motorized/Module
Viewing angle	43° -15°	107°	78°	87°	77°	104.7° -56.1°
Night vision type	Smart IR	Smart LED	Smart LED	Smart LED	Smart LED	Smart LED
IR Range	4 IR LEDs/120m	1 Warmlight LED/15m	1 Warmlight LED/15m	1 Warmlight LED/30m	1 IR LEDs/30m	4 IR LEDs/70m
WDR	Ultra WDR 140db, Ai ISP, Ai SSA, EIS, Defog, LDC, SVC, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area	BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Plastic & Metal	Plastic & Metal	Plastic & Metal	Plastic & Metal	Metal	Metal
SD Card	Micro SD 1TB, Dahua Cloud, FTP, SFTP, NAS	Dahua Cloud, FTP, SFTP, NAS	Dahua Cloud, FTP, SFTP, NAS	Dahua Cloud, FTP, SFTP, NAS	Micro SD 256GB, Dahua Cloud, FTP, SFTP, NAS	Micro SD 512GB, Dahua Cloud, FTP, SFTP, NAS
Degree of protection	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security
Temperature	- 30 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 30 ° C to + 60C
Voltage	%30±DC12V/3.7W- Max 9.8W	%30±DC12V/1.2W- Max 4.2W	%30±DC12V/1W- Max 4.3W	%30±DC12V/1.5W- Max 3.4W	%30±DC12V	%30±DC12V/2.7W- Max 11.3W
Price	505,000,000	95,500,000	125,500,000	98,300,000	262,000,000	578,000,000



	T1E-29A-IL	T1E-49A-IL	HDW1239T1P-A-IL-S6	HFW1639TC-A-IL	HDW1639T-A-IL	HFW2849S-S-IL
Resolution	2MP 1/2.8"	4MP 1/3"	2MP 1/2.8"	6MP 1/2.7"	6MP 1/2.7"	4K 1/2.7"
Microphone	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic
Lens	2MP 2.8mm fixed/M12	4MP 2.8mm fixed/M12	2MP 2.8mm fixed/M12	6MP 3.6mm fixed/M12	6MP 3.6mm fixed/M12	4K 3.6mm fixed/M12
Viewing angle	105°	94°	103°	91°	110°	87°
Night vision type	Smart Dual Light+	Smart Dual Light+	Smart Dual Light+	Smart Dual Light+	Smart Dual Light+	Smart Dual Light+
IR Range	1 IR LED/30m 1 Warmlight LED/15m	1 IR LED/30m 1 Warmlight LED/15m	1 Multi-core LED IR/30m - Warmlight/30m	1 Multi-core LED IR/30m - Warmlight/30m	1 Multi-core LED IR/30m - Warmlight/30m	1 IR LED/30m 1 Warmlight LED/30m
WDR	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Plastic	Plastic	Plastic & Metal	Metal	Metal	Metal
SD Card	Dahua Cloud, FTP	Dahua Cloud, FTP	Dahua Cloud, FTP	Dahua Cloud, FTP	Dahua Cloud, FTP	Micro SD 256GB, Dahua Cloud, FTP, SFTP, NAS
Degree of protection	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security
Temperature	- 40 ° C to + 50C	- 40 ° C to + 50C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 55C
Voltage	%30±DC12V/1.4W- Max 3.4W	%30±DC12V/1.4W- Max 3.3W	%30±DC12V/1W- Max 4.3W	%30±DC12V/2W- Max 4W	%30±DC12V/2W- Max 4W	%30±DC12V/2.7W- Max 5W
Price	87,100,000	95,200,000	101,200,000	158,100,000	158,100,000	227,000,000



	HFW2549T-AS-IL	HFW2849T-ZAS-IL	HFW2449TL-S-PRO	HFW2849TL-S-PRO	HDW2449T-S-PRO	HFW2549TL-S-PV
Resolution	5MP 1/2.7"	4K 1/2.9"	4MP 1/1.8"	4K 1/1.8"	4MP 1/1.8"	5MP 1/2.7"
Microphone	1/1 Bult In Mic	1/1 Bult In Mic	Bult In Mic	Bult In Mic	Bult In Mic	Built-in Mic & Speaker
Lens	5MP 3.6mm fixed/M12	4MP 2.7-13.5mm Motorized/ φ 14	4MP 2.8mm fixed/M12	4K 2.8mm fixed/M12	4MP 2.8mm fixed/M12	5MP 3.6mm fixed/M12
Viewing angle	92°	114° -32°	105°	110°	105°	91.9°
Night vision type	Smart Dual Light+	Smart Dual Light+	Wiz Color	Wiz Color	Wiz Color	Smart Dual Light+
IR Range	2 IR LEDs/60m 2 Warmlight LEDs/50m	2 IR LEDs/60m 2 Warmlight LEDs/60m	4 Warmlight LEDs/50m	4 Warmlight LEDs/50m	2 Warmlight LEDs/30m	2 IR LED/30m 2 Warmlight LED/30m
WDR	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, RoI, Privacy Area, Smart Dual Illumination
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal	Metal	Metal	Metal	Metal+Plastic	Metal
SD Card	Micro SD 256GB Dahua Cloud, FTP, SFTP	Micro SD 256GB Dahua Cloud, FTP, SFTP	Micro SD 256GB Dahua Cloud, FTP, SFTP, NAS	Micro SD 256GB Dahua Cloud, FTP, SFTP, NAS	Micro SD 256GB Dahua Cloud, FTP, SFTP, NAS	Micro SD 256GB, Dahua Cloud, FTP, SFTP, NAS
Degree of protection	IP67/IK10/Low Anti Corrosion 4KV Lightning, Cyber Security	IP67/IK10/Low Anti Corrosion 4KV Lightning, Cyber Security	IP67/IK10/Low Anti Corrosion 4KV Lightning, Cyber Security	IP67/IK10/Low Anti Corrosion 4KV Lightning, Cyber Security	IP67/IK10/Low Anti Corrosion 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security
Temperature	- 40 ° C to + 60C	- 30 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 55C
Voltage	%30±DC12V/2.3W- Max 6.7W	%30±DC12V/2.6W- Max 10.2W	%30±DC12V/1.4W- Max 5.4W	%30±DC12V/2.3W- Max 6.1W	%30±DC12V/1.7W- Max 4.9W	%30±DC12V/2.1W- Max 11.6W
Price	249,800,000	445,800,000	178,300,000	271,500,000	178,300,000	199,500,000




	HFW3549T1-AS-PV	HFW3849T1-AS-PV-S4	PFW3849S-A180-AS-PV	SD2A500NB-GNY-A-PV	PTS2249B-E2-S-PV-PRO	SDT4E4-425F-GB-A-PV1
Resolution	5MP 1/2.7"	4K 1/2.8"	4K 1/2.7"	5MP 1/2.8"	2MP 1/2.9"	4MP 1/2.8"
Microphone	Built-in Mic & Speaker Dual	Built-in Mic & Speaker Dual	Built-in Mic & Speaker Dual	Built-in Mic & Speaker	Built-in Mic & Speaker	1/1+ Built-in Mic & Speaker
Lens	5MP 3.6mm fixed/M12	4K 3.6mm fixed/M12	4K 2.8mm fixed/M12	5MP 4mm fixed/M12	2MP 3.6mm fixed/M12	Panorama: 2.8mm F1.0 Detail: 5mm 1/25-mm F1.6 - F3.6
Viewing angle	78°	85°	180°	80.4°	81°	Panorama: ° 101 Detail: ° 51.9-° 3.0
Night vision type	Smart Dual Light+	Smart Dual Light+	Smart Dual Light+	Smart Dual Light+	Wiz Color Smart Dual Light+	Smart Dual Light+
IR Range	2 IR LEDs/30m 2 Warmlight LEDs/30m	2 IR LEDs/30m 2 Warmlight LEDs/30m	2 IR LEDs/25m 2 Warmlight LEDs/20m	2 IR LEDs/30m 2 Warmlight LEDs/30m	4 Warmlight LEDs/30m	2 IR LED/30m 2 Warmlight LED/30m
WDR	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area, Smart Dual Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area, Smart Dual Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area, Smart Illumination	DWDR, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area, Smart Dual Illumination	True WDR 120db, BLC, HLC, 3D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto/Manual IRIS, Rol, Privacy Area, Smart Dual Illumination
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal+Plastic	Metal+Plastic	Metal	Plastic	Plastic	Metal
SD Card	Micro SD 256GB Dahua Cloud, FTP, SFTP	Micro SD 256GB Dahua Cloud, FTP, SFTP	Micro SD 256GB Dahua Cloud, FTP, SFTP, NAS	Micro SD 256GB Dahua Cloud, FTP	Micro SD 256GB Dahua Cloud, FTP, SFTP, NAS	Micro SD 512GB Dahua Cloud, FTP, SFTP, NAS
Degree of protection	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP67 4KV Lightning, Cyber Security	IP66/TVS 2000V lightning, Surge, Voltage, Transient, Waterproof & Dustproof, Cyber Security	IP66 4KV Lightning, Cyber Security	IP66, TVS 6000V Lightning, Surge Voltage Transient, Cyber Security
Temperature	- 40 ° C to + 60C	- 40 ° C to + 60C	- 40 ° C to + 60C	- 30 ° C to + 55C	- 40 ° C to + 50C	- 40 ° C to + 65C
Voltage	%30±DC12V/3.3W- Max 6.8W	%30±DC12V/4.5W- Max 7.2W	%30±DC12V/3.4W- Max 9W	12 VDC/1.5 A ± %10 PoE (802.3af) Basic: 3.5 W; Max: 10 W (illuminator)	%30±DC12V/2.3W- Max 9.2W	%30±DC12V/%10± 3A/PoE(802.3at) Basic 12W/Max 25W
Price	341,000,000	418,500,000	547,000,000	149,900,000	295,900,000	912,000,000



						
	SD3A205-GNP-PV	SD49225XA-HNR-S3	SD49225DB-HNY	SD49425ZB-HNR	SD49425XB-HNR	SD5A232XA-HNR
Resolution	2MP 1/2.8"	2MP 1/2.8"	2MP 1/2.8"	4MP 1/2.8"	4 MP 1/2.8"	2 MP 1/2.8"
Microphone	Built-in Mic & Speaker	Built-in Mic & Speaker Dual	Built-in Mic & Speaker Dual	Built-in Mic & Speaker	Built-in Mic & Speaker	1/1
Lens	2MP 13.5-2.7mm F1.8 – F3.3	2MP 4.8mm – 120mm	2MP 4.8mm – 120mm	4MP 4.8mm – 120mm	4MP 4.8mm – 120mm	2MP 4.9mm – 156mm F1.35 – F4.4
Viewing angle	101.6° – 33.5°	56.2° – 2.6°	58.5° – 2.8°	55.8° – 2.4°	60.0° – 2.5°	62.8° – 2.2°
Night vision type	Smart IR	Smart IR	Smart IR	Smart IR	Smart IR	Smart IR
IR Range	4 IR LEDs/30m 1 White light	4 IR LEDs/100m	3 IR LEDs/100m	4 IR LEDs/100m	4 IR LEDs/100m	4 IR LEDs/150m
WDR	DWDR, BLC, HLC, 3D/2D DNR, AWB, AGC, Fixed IRIS, Rol, Privacy Area, Smart Illumination	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, Rol, Privacy Area, Smart. Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, Rol, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, Rol, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, Rol, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, Rol, Privacy Area, Smart Illumination, Zoom Prio
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Metal	Aluminum alloy ADC12	Aluminum alloy ADC12	Aluminum alloy ADC12	Aluminum alloy ADC12	Aluminum alloy ADC12
SD Card	Micro SD 256GB Dahua Cloud, FTP, NAS	Micro SD 512GB Dahua Cloud, FTP, NAS	Micro SD 512GB Dahua Cloud, FTP, NAS	Micro SD 512GB . Dahua Cloud, FTP, SFTP, NAS, Local PC	Micro SD 512GB . Dahua Cloud, FTP, SFTP, NAS, Local PC	Micro SD 256GB Dahua Cloud, FTP, NAS
Degree of protection	IP66/TVS 2000V Lightning, Surge Voltage Transient, Cyber Security	IP6/66KV Lightning, Surge, Voltage Transient Cyber Security	IP6/66KV Lightning, Surge, Voltage Transient Cyber Security	IP6/66KV Lightning, Surge, Voltage Transient Cyber Security	IP6/66KV Lightning, Surge, Voltage Transient Cyber Security	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Security
Temperature	- 30 ° C to + 60C	- 40 ° C to + 65C	- 40 ° C to + 60C	- 40 ° C to + 70C	- 40 ° C to + 70C	- 40 ° C to + 70C
Voltage	%30±DC12V/2A %10± Basic: 5W Max: 12W	%30±DC12V/ 3A %10±/PoE+ (802.3at) Basic: 12W Max.: 21W	%30±DC12V/ 3A %10±/PoE+ (802.3at) Basic: 12W Max.: 20W	%30±DC12V/ 3A %10±/PoE+ (802.3at) Basic: 9.8W Max.: 20W	%30±DC12V/ 3A %10±/PoE+ (802.3at) Basic: 13W Max.: 21W	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 12W Max.: 20W
Price	289,000,000	667,000,000	667,000,000	806,000,000	806,000,000	1,268,000,000



						
	SD5A232XB-HNR	SD5A432XA-HNR	SD5A432XB-HNR	SD5A432GB-HNR	SD5A445GB-HNR	SD5A445XA-HNR
Resolution	2MP 1/2.8"	4MP 1/2.8"	4MP 1/2.8"	4MP 1/2.8"	4 MP 1/2.8"	4 MP 1/2.8"
Microphone	1/1	1/1	1/1	1/1	1/1	1/1
Lens	2MP 4.8mm – 154mm F1.6 – F4.0	4MP 4.9mm – 156mm F1.35 – F4.4	4MP 4.8mm – 154mm F1.6 – F4.0	4MP 4.8mm – 154mm F1.6 – F4.0	4MP 3.95mm – 177.7mm F1.6 – F4.95	4MP 3.95mm – 177.7mm F1.6 – F4.95
Viewing angle	58.44° – 3.04°	61.6° – 2.1°	55.81° – 2.37°	55.8° – 2.4°	65.7° – 1.9°	70.3° – 1.8°
Night vision type	Smart IR	Smart IR	Smart IR	Smart IR	Smart IR	Smart IR
IR Range	4 IR LEDs/150m	4 IR LEDs/150m	4 IR LEDs/150m	4 IR LEDs/150m	4 IR LEDs/150m	4 IR LEDs/150m
WDR	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, RoI, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, RoI, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, RoI, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, RoI, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, RoI, Privacy Area, Smart Illumination, Zoom Prio	True WDR 120db, BLC, HLC, 3D/2D DNR, AWB, AGC, Auto IRIS, RoI, Privacy Area, Smart Illumination, Zoom Prio
Compression format	H.265+	H.265+	H.265+	H.265+	H.265+	H.265+
Body material	Aluminum alloy ADC12	Aluminum alloy ADC12	Aluminum alloy ADC12	Aluminum alloy ADC12	Aluminum alloy ADC12	Metal
SD Card	Micro SD 512GB Dahua Cloud, FTP, NAS	Micro SD 256GB Dahua Cloud, FTP, NAS	Micro SD 512GB Dahua Cloud, FTP, NAS	Micro SD 512GB . Dahua Cloud, FTP, SFTP, NAS, Local PC	Micro SD 512GB Dahua Cloud, FTP, NAS	Micro SD 256GB Dahua Cloud, FTP
Degree of protection	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Securit	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Securit	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Securit	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Securit	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Security	IP67/IK6/10KV Lightning, Surge, Voltage Transient Cyber Security
Temperature	- 30 ° C to + 70C	- 40 ° C to + 70C	- 40 ° C to + 70C	- 40 ° C to + 70C	- 40 ° C to + 70C	- 40 ° C to + 70C
Voltage	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 13W Max.: 22W	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 12W Max.: 20W	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 13W Max.: 22W	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 13W Max.: 22W	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 10W Max.: 22W	%30±DC24V/ 2.5A %25±/PoE+ (802.3at) Basic: 11W Max.: 20W
Price	1,268,000,000	1,328,000,000	1,362,000,000	1,424,000,000	1,702,000,000	1,670,000,000



SD6CE445XA-HNR

EBW-8842AS

Resolution

4MP 1/2.8"

4K 1/1.7"

Microphone

1/1

1/1 Dual
Built-in Mic & Speaker

Lens

4MP 3.95mm – 177.7mm
F1.6 – F4.95

4K 1.85mm fixed/M12

Viewing angle

70.3° – 1.8°

H: ° 185 - V: ° 180

Night vision type

Smart IR

Smart IR

IR Range

6 IR LEDs/250m

3 IR LEDs/10m

WDR

True WDR 120db, BLC, HLC, 3D/2D
DNR, AWB, AGC, Auto IRIS, Rol, Privacy
Area, Smart Illumination, Zoom Prio

DWDR, BLC, HLC, 3D DNR, AWB, AGC,
Fixed IRIS, Rol, Privacy Area, Smart
Illumination, Defog

Compression format

H.265+

H.265+

Body material

Metal

Metal

SD Card

Micro SD 256GB
Dahua Cloud, FTP, NAS, Local PC

Micro SD 256GB
Dahua Cloud, FTP, SFTP, NAS

Degree of protection

IP67/IK6/10KV Lightning, Surge,
Voltage Transient Cyber Security

IP67/IK4/10KV Lightning
Cyber Security

Temperature

- 40 ° C to + 70C

- 40 ° C to + 60C

Voltage

%30±DC24V/ 2.5A %25±/PoE+
(802.3at)
Basic: 13W Max.: 26W

%30±DC12V/6.5W-Max 13W
PoE(802.3at)6.1W-Max 13.9W

Price

1,737,000,000

995,000,000



NVR4216-4KS3

NVR4108HS-EI

NVR4108HS-4KS2/L

NVR1108HS-S3/H

NVR4104HS-4KS2/L

NVR2104HS-I2

Compression format

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

Number of channel

16CH

8CH

8CH

8CH

4CH

4CH

BandWidth / Recording

160Mbps

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Image quality

Up To 12MP

Up To 16MP

Up To 8MP

Up To 8MP

Up To 8MP

Up To 12MP

Screen output

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

SD Card

2*20TB

16TB

10TB

8TB

10TB

10TB

Number of network port

1*100M

1*100M

1*100M

1*100M

1*100M

1*100M

POE

--

--

--

--

--

--

Number of USB port

2 USB2.0

2 USB2.0

2 USB2.0

2 USB2.0

2 USB2.0

2 USB2.0

Voltage

DCV12/4A

DCV12/2A

DCV12/2A

DCV12/2A

DCV12/2A

DCV12/2A

Price

318,300,000

285,000,000

207,000,00

133,000,000

157,000,000

169,000,000



NVR5432-16P-EI

NVR5432-EI

NVR5232-EI

NVR4232-EI

NVR4232-4KS2/L

NVR5216-EI

Compression format

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

Number of channel

32CH

32CH

32CH

32CH

32CH

16CH

BandWidth / Recording

160Mbps

384Mbps

384Mbps

256Mbps

160Mbps

384Mbps

Image quality

Up To 32MP

Up To 32MP

Up 8 32MP

Up To 16MP

Up To 8MP

Up To 32MP

Screen output

2*HDMI(3840*2160)/VGA

2*HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

SD Card

4*20TB

4*20TB

2*20TB

2*10TB

2*10TB

2*20TB

Number of network port

2*1000M

2*1000M

1*1000M

1*1000M

1*1000M

1*1000M

POE

16 Port

--

--

--

--

--

Number of USB port

3 (1USB2.0 / 2USB3.0)

3 (1USB2.0 / 2USB3.0)

2 (1USB2.0 / 1USB3.0)

2*1USB2.0

2* USB2.0

2 (1USB2.0 / 1USB3.0)

Voltage

100-240VAC,50-60Hz

100-240VAC,50-60Hz

VDC12V/4A

VDC12V/4A

VDC12V/4A

VDC12V/4A

Price

1,300,000,000

1,163,000,000

897,500,000

509,500,000

450,000,000

653,000,000



NVR608RH-128-XI

NVR608H-64-XI

NVR5864-EI

NVR608H-32-XI

Compression format

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

AI Coding/H.265+

Number of channel

128CH

64CH

64CH

32CH

BandWidth / Recording

1280Mbps

1280Mbps

384Mbps

1280Mbps

Image quality

Up To 32MP

Up To 32MP

Up 8 32MP

Up To 32MP

Screen output

4*HDMI(3840*2160)/VGA

4*HDMI(3840*2160)/VGA

HDMI(3840*2160)/VGA

4*HDMI(3840*2160)/VGA

SD Card

8*20TB

8*20TB

8*20TB

8*20TB

Number of network port

2*1000M

2*1000M

2*1000M

2*1000M

POE

--

--

--

--

Number of USB port

4 (2USB2.0 / 2USB3.0)

4 (2USB2.0 / 2USB3.0)

2 (2USB2.0 / 2USB3.0)

2 (2USB2.0 / 2USB3.0)

Voltage

100-240VAC,50-60Hz

100-240VAC,50-60Hz

100-240VAC,50-60Hz

100-240VAC,50-60Hz

Price

4,750,000,000

3,360,000,000

1,870,000,000

2,380,000,000



	DHI-NVR1104HS-S3/H (V2.0)	NVR2108HS-S3	NVR2108HS-4KS3	NVR4116HS-4KS3	NVR2216-I2
Type	4CH 1U Compact Lite NVR	8CH 1U Compact Lite NVR	8CH 1U Compact Lite NVR	16CH 1U Compact Lite NVR	16CH 1U Compact Ai NVR
Encode Capacity	4ch 4K@30fps	8ch 4K@30fps	8ch 4K@30fps	16ch 12MP@30fps	16ch 12MP@30fps
Decode Capacity	Max 4K@30fps	Max 12MP@30fps	Max 12MP@30fps	Ai Disabled: 1ch 12MP@30fps 2ch 8MP@30fps Ai Enabled: 1ch 12MP@30fps 1ch 8MP@30fps	Ai Disabled: 1ch 12MP@30fps 2ch 8MP@30fps Ai Enabled: 1ch 8MP@30fps
BandWidth	80/80/60Mbps	80/80/60Mbps	80/80/60Mbps	Ai Disabled: 80/160/160Mbps Ai Enabled: 60/80/80Mbps	Ai Disabled: 72/144/144Mbps Ai Enabled: 36/72/72Mbps
Video Compression	Smart H.+265 Dual Stream	Smart H.+265, MJPEG Dual Stream	Smart H.+265, MJPEG Dual Stream	Smart H.+265 Dual Stream	Smart H.+265 Dual Stream
Audio Codec	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726, AAC
Video Output	Simultaneous 1 HDMI, 1 VGA 1080P	Simultaneous 1 HDMI, 1 VGA 1080P	Simultaneous 1 HDMI 4K, 1 VGA 1080P	Simultaneous 1 HDMI 4K 1 VGA 1080P	Simultaneous 1 HDMI 4K 1 VGA 1080P
Access Protocols	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P
Network Interface	1*10 / 100Mbps	1*10 / 100Mbps	1*10 / 100Mbps	1*10 / 100 / 1000Mbps	1*10 / 100 / 1000Mbps
Storage	1 SATA Port, 8TB	1 SATA Port, 16TB	1 SATA Port, 20TB	1 SATA Port, 20TB	2 SATA Port, Each Disk 10TB Max Capacity 20TB
Number of USB port	2*USB 2.0	2*USB 2.0	2*USB 2.0	2*USB 2.0	2*USB 2.0
Temp/Humidity	-10° ~ +45° C / 10 - 93%	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%
Voltage	12VDC/1.5A/10W (Without HDD)	12VDC/1.5A/10W (Without HDD)	12VDC/1.5A/10W (Without HDD)	12VDC/2A/10W (Without HDD)	12VDC/4A/10W (Without HDD)
Price	109,900,000	189,500,000	204,000,000	285,500,000	31,820,000



NVR2108HS-I2

NVR2116HS-I2

NVR4432-EI

NVR5832-EI

NVR5464-EI

Type	8CH 1U Compact Ai NVR	16CH 1U Compact Lite NVR	32CH 1U WizSense NVR	32CH 2U WizSense NVR	64CH 2U WizSense NVR
Encode Capacity	8ch 12MP@30fps	16ch 12MP@30fps	16MP@30fps	32MP@30fps	32MP@30fps
Decode Capacity	AI Disabled: 1ch 12MP@30fps 1ch 8MP@30fps AI Enabled: 1ch 8MP@30fps	AI Disabled: 1ch 12MP@30fps 1ch 8MP@30fps AI Enabled: 1ch 8MP@30fps	AI Disabled: 32MP@30fps AI Enabled: 16MP@30fps 24MP@30fps	AI Disabled: 64MP@30fps AI Enabled: 32MP@30fps	AI Disabled: 64MP@30fps AI Enabled: 32MP@30fps
BandWidth	80/80/60Mbps	80/80/60Mbps	AI Disabled: 256/256/256Mbps AI Enabled: 180/180/180Mbps	AI Disabled: 384/384/384Mbps AI Enabled: 200/200/200Mbps	AI Disabled: 384/384/384Mbps AI Enabled: 200/200/200Mbps
Video Compression	Smart H.+265 Dual Stream	Smart H.+265, MJPEG Dual Stream	Smart H.+265, MJPEG Dual Stream	Smart H.+265 Dual Stream	Smart H.+265 Dual Stream
Audio Codec	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726	PCM, G711A, G711U, G726
Video Output	Simultaneous 1 HDMI 4K, 1 VGA 1080P	Simultaneous 1 HDMI 4K, 1 VGA 1080P	Simultaneous/Heterogeneous 1 HDMI 4K 1 VGA 1080P	Simultaneous/Heterogeneous 2 HDMI 4K 2 VGA 1080P	Simultaneous/Heterogeneous 2 HDMI 4K 2 VGA 1080P
Access Protocols	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), Panasonic, Sony, Axis, Arecont, Pelco, Canon, Hanwha, RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), Panasonic, Sony, Axis, Arecont, Pelco, Canon, Hanwha, RTSP, CGI, SDK, API, P2P	ONVIF(S,T,G), Panasonic, Sony, Axis, Arecont, Pelco, Canon, Hanwha, RTSP, CGI, SDK, API, P2P
Network Interface	1*10 / 100Mbps	1*10 / 100/1000Mbps	2*10 / 100 / 1000Mbps	2*10 / 100 / 1000Mbps	2*10 / 100 / 1000Mbps
Storage	1 SATA Port, 10TB	1 SATA Port, 10TB	4SATA Port, Each Disk 20TB	8SATA Port, Each Disk 20TB	4SATA Port, Each Disk 20TB
Number of USB port	2*USB 2.0	2*USB 2.0	2*USB 1/2.0* USB 3.0	2*USB 2/2.0* USB 3.0	1*USB 2/2.0* USB 3.0
Temp/Humidity	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%	-10° ~ +55° C / 10 - 93%
Voltage	12VDC/1.5A/10W (Without HDD)	12VDC/1.5A/10W (Without HDD)	240-100VAC, 60-50Hz 10W(Without HDD)	240-100VAC, 60-50Hz 13W(Without HDD)	240-100VAC, 60-50Hz 13W(Without HDD)
Price	285,600,000	245,200,000	816,000,000	1,565,000,000	1,346,500,000



NVR5864H-XI

NKB1000

Type	64CH 2U WizMind NVR	Type	Network Keyboard
Encode Capacity	32MP@30fps	Keyboard / Key panel	Electromechanical
Decode Capacity	AI Disabled: 64MP@30fps AI Enabled:32MP@30fps	Joystick	-3axis, vector-solving, with twisting, return to-center hea
BandWidth	80/80/60Mbps	Keyboard Connector	RJ45-, RS232, RS485, RS422 (reserved), USB
Video Compression	Smart H.+265 Dual Stream	Keyboard Communication	Direct Mode, Network Mode
Audio Codec	PCM, G711A, G711U, G726	Display	LCD, 75.2mm×33.85mm
Video Output	Simultaneous 2 HDMI 4K, 2 VGA 1080P	Max Number of Users	64 (including "admin")
Access Protocols	ONVIF(S,T,G), Panasonic, Sony, Axis, Arecont, Pelco, Canon, Hanwha, RTSP, CGI, SDK, API, P2P	Weight	1.3kg (Including package)
Network Interface	2*10 / 100/1000Mbps	Max RS485 Addresses	256
Storage	8SATA Port, Each Disk 20TB	Max Number of PTZ	2048
Number of USB port	2*USB 2/2.0* USB 3.0	Temperature	-10°C~+55°C
Temp/Humidity	-10° ~ +55° C / 10 - 93%	Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A
Voltage	240-100VAC, 60-50Hz 13W(Without HDD)	Power Consumption	5W
Price	2,630,000,000	Price	441,000,000



فروش محصولات داهوا

📞 اکبر کشاورز ۰۹۱۲۹۴۹۴۲۳۴ | فاطمه واحدی ۰۹۹۰۲۷۰۶۲۵۷

🌐 www.rayannovincctv.com | 📷 [rayannovin.cctv](https://www.instagram.com/rayannovin.cctv)

📍 تهران، خیابان جمهوری، تقاطع شیخ هادی و رازی، مرکز تجاری یگانه، طبقه دوم، واحد ۲۱۱

 **RAYAN
NOVIN**